

Temperature Controller

■ AX series Multi input digital temperature controller

Specification

Model	AX9	AX2	AX7	AX3	AX4
Appearance					
W×H×D (mm)	96 X 96 X 63	48 X 96 X 63	72 X 72 X 63	96 X 48 X 63	48 X 48 X 63
Input type	Multi input (Thermocouple: K, J, R, T, IEC 584-1), (RTD: Pt 100 Ω, IEC751)				
Sampling cycle		100 ms			
Input impedance		max 1 MΩ			
Allowable input voltage		10 V d.c. max			
Display accuracy	±0.3 % of FS ±1 digit (In case of R type, ±1.0 % of ±1 digit in the 0 ~ 600 °C range)				
Display type	7 Segment LED (PV: red, SV: green)				
Front Size (mm)	PV 22.5×11.2	14.5×7.0	14.5×7.0	15.9×7.6	13.0×6.5
	SV 18.7×9.3	10.8×5.2	9.4×4.7	12.0×6.0	9.2×5.2
Input	• Thermocouple : 0.1 °C (TC-K2, TC-J), 0.5 °C (TC-K1) • RTD : 0.03 °C, (0.1 °F)				
Insulation resistance	min 20 MΩ, 500 V d.c. 1 minute (primary terminal–secondary terminal)				
Dielectric strength	2300 V a.c. 50/60 Hz, for 1min (primary terminal–secondary terminal)				
Control method	PID control by Auto-Tuning, ON / OFF control.				
Control output operation	Reverse operation / Direct operation selectable by the parameter setting				
Control output	• Relay output ※Selectable by the parameter setting 1a contact, 3A 240 V a.c., 3 A 30 V d.c. (resistive load) • Voltage pulse output for running SSR [time sharing proportional control (CYC)] • Voltage pulse output for running SSR 0/12 V d.c., pulse voltage (resistive load minimum 600 Ω)				
Power supply voltage	100 – 240 V a.c. 50 / 60 Hz				
Voltage fluctuation	± 10 % of the power supply voltage				
Power consumption	Within 5.5 VA				
Ambient temperature	– 5 ~ 50 °C				
Ambient humidity	35 ~ 85 % R.H (but without dew condensation)				
Vibration resistance	10 – 55 Hz, 0.75 mm, each to direction X, Y and Z for 2 hours				
Shock resistance	300 m/s² to direction 6 each 3 times				
Weight (Weight included the weight of box)	320 g	320 g	180 g	300 g	400 g

Suffix Code

Model	Code	Information	
AX	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	Digital temperature controller (Multi input: K, J, Pt100 Ω)	
Dimension	2	AX2 : 48 X 96 mm	
	3	AX3 : 96 X 48 mm	
	4	AX4 : 48 X 48 mm	
	7	AX7 : 72 X 72 mm	
	9	AX9 : 96 X 96 mm	
Output selection	1	SSR + Relay1 + Relay2	Relay or SSR as control output (Selectable in operator setup mode)
	2	SSR + Relay1 + Relay2 + Relay3	
	1B	SSR + Relay1 (Form c) + Relay2	Only for AX2, 3, 7, 9
	2B	SSR + Relay1 (Form c) + Relay2 + Relay3	
	3	4 – 20 mA + Relay2	Current output as control output
	4	4 – 20 mA + Relay2 + Relay3	
Power supply voltage	A	100 – 240 V a.c. 50 / 60 Hz	

※ Form C : Normal close type contact.

※ Relay output operates as control output, alarm output and LBA output depending on the internal parameter setting.