



Network module, Modicon M580, FactoryCast Ethernet

BMENOC0311

Product availability: Stock - Normally stocked in distribution facility

Main

Range of Product	Modicon M580
Product or Component Type	Communication module
Product compatibility	BMEXBP Ethernet + X-bus rack
Concept	Transparent Ready

Complementary		
Integrated connection type	3 Ethernet RJ45 10/100 Mbit/s double shielded twisted pair	
Web server	Advanced	
Transmission support medium	Ethernet backplane	
Communication service	Bandwidth management FDR server SNMP network administrator Modbus TCP I/O Scanner and Messaging Ethernet/IP I/O Scanner and Messaging RSTP support Port mirroring Embedded multiport switch	
Web services	FactoryCast configurable	
Port Ethernet	10BASE-T/100BASE-TX	
Supply	Internal power supply via rack	
Marking	CE	
Module format	Standard	
Current consumption	900 mA 3.3 V DC for product version >= 13) 1800 mA 3.3 V DC for product version < 13)	
Net Weight	0.44 lb(US) (0.2 kg)	

Environment

Ambient air temperature for operation	32140 °F (060 °C)	
IP Degree of Protection	IP20	
Directives	2014/35/EU - low voltage directive 2014/30/EU - electromagnetic compatibility	
Local signalling	for processor running (RUN) 1 LED (green) for processor or system fault (ERR) 1 LED (red) for ETH MS (Ethernet port configuration status) 1 LED (green/red) for Eth NS (Ethernet network status) 1 LED (green/red)	

Ordering and shipping details

Category	18160-MODICON M340
Discount Schedule	PC34
GTIN	3606480713927
Nbr. of units in pkg.	1
Package weight(Lbs)	8.82 oz (250.0 g)
Returnability	Yes
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	2.17 in (5.5 cm)
Package 1 width	4.33 in (11.0 cm)
Package 1 Length	4.57 in (11.6 cm)
Unit Type of Package 2	S02
Number of Units in Package 2	15
Package 2 Weight	9.01 lb(US) (4.088 kg)
Package 2 Height	5.91 in (15.0 cm)
Package 2 width	11.81 in (30.0 cm)
Package 2 Length	15.75 in (40.0 cm)

Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End of Life Information	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.	


Product data sheet

BMENOC0311

Dimensions Drawings

Modules Mounted on Racks

Dimensions



- (1) With removable terminal block (cage, screw or spring).
- (2) With FCN connector.
- (3) On AM1 ED rail: 35 mm wide, 15 mm deep. Only possible with BMXXBP0400/0400H/0600/0600H/0800/0800H rack.

Rack references	a in mm	a in in.
BMXXBP0400 and BMXXBP0400H	242.4	09.54
BMXXBP0600 and BMXXBP0600H	307.6	12.11
BMXXBP0800 and BMXXBP0800H	372.8	14.68
BMXXBP1200 and BMXXBP1200H	503.2	19.81