Analogue output cartridge, Modicon M221, 2 analog current outputs, I/O extension

TMC2AQ2C

Main

Range of product	Modicon M221
Product or component type	Analogue output cartridge
Product compatibility	Modicon M221C
Complementary	

Complementary			
Analogue output number	2		
Analogue output type	Current: 420 mA		
Analogue output resolution	12 bits		
LSB value	3.91 µA 420 mA current		
Load type	Resistive		
Load impedance ohmic	<= 500 Ohm		
Conversion time	20 ms		
Stabilisation time	40 ms		
Absolute accuracy error	+/- 1 % of full scale +/- 0.3 % of full scale at 25 °C		
Temperature drift	+/- 0.02 %FS/°C		
Repeat accuracy	+/- 0.4 %FS		
Non-linearity	+/- 0.01 %FS		
Cross talk	<= 1 LSB		
Type of cable	Twisted shielded pairs cable		
Electrical connection	3 x 1.5 mm² 2 screw terminal blocks with pitch 3.81 mm adjustment for outputs		
Maximum cable distance between devices	Twisted shielded pairs cable: <30 m for output		
Insulation	Non-insulated between analogue output and internal logic		
Height	41 mm		
Depth	15 mm		
Width	35 mm		
Net weight	0.015 kg		

Environment

Immunity to microbreaks	10 ms		

Packing Units

<u> </u>	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	20.0 g
Package 1 Height	3.5 cm
Package 1 width	7.0 cm
Package 1 Length	4.6 cm
Unit Type of Package 2	S02
Number of Units in Package 2	75
Package 2 Weight	3.364 kg
Package 2 Height	15.0 cm
Package 2 width	30.0 cm
Package 2 Length	40.0 cm

Offer Sustainability

Green Premium product		
REACh Declaration		
Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration		
Yes		
Yes		
Yes		
China RoHS declaration		
Product Environmental Profile		
End of Life Information		
Yes		
WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov		