


Product data sheet

Specifications



speed monitoring module - RS422 - 5V

VW3A3620

Main

Range of product	Altivar
Product or component type	Encoder interface module
Range compatibility	Altivar 32 Altivar Machine ATV320
[Us] rated supply voltage	5 V (voltage limits: 5...5.5 V)
Number of pulses per revolution	3600 for ATV32

Complementary

Product compatibility	ATV32 (>= V1.8)
Protection type	Overload protection Short-circuit protection
Maximum operating frequency	250 kHz
Input signal	TTL
Electrical connection	Terminal, connection capacity: 1.5 mm² (AWG 16), encoder, 200 mA
Net weight	0.3 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	56.0 g
Package 1 Height	4.7 cm
Package 1 width	6.5 cm
Package 1 Length	9.0 cm
Unit Type of Package 2	S03
Number of Units in Package 2	96
Package 2 Weight	5.97 kg
Package 2 Height	30.0 cm
Package 2 width	30.0 cm
Package 2 Length	40.0 cm

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov