Product data sheet

Specifications





Limit switch body, Limit switches XC Standard, ZCP, compact, 1NC+1 NO, snap action

ZCP21

Ν	V	1	а	ı	r

Range of product	Telemecanique Limit switches XC Standard
Series name	Standard compact
Product or component type	Limit switch body
Device short name	ZCP
Design	Compact
Body type	Fixed
Associated head	ZCE06
Associated flead	
	ZCE28
	ZCE63
	ZCE01
	ZCE02
	ZCE66
	ZCE14
	ZCE11
	ZCE27
	ZCEH2
	ZCE09
	ZCE67
	ZCE08
	ZCE07
	ZCE24
	ZCEH0
	ZCE21
	ZCE64
	ZCE29
	ZCE62
	ZCE65
	ZCE13
	ZCE10
	ZCE05
Body material	Plastic
Number of poles	2
Contacts type and composition	1 NC + 1 NO
Contact operation	Snap action

Complementary

Associated connection component	ZCPEP20 ZCPEN12 ZCPEF12 ZCPEG11 ZCPEP16 ZCPEG13	
Electrical connection	Screw-clamp terminals, clamping capacity: 1 x 0.342 x 1.5 mm²	_
Contacts insulation form	Zb	

Contacts material	Silver plated contacts		
Positive opening	With		
Minimum actuation speed	0.01 m/s		
Contact code designation	B300, AC-15 (Ue = 240 V), le = 1.5 A conforming to EN/IEC 60947-5-1 appendix A R300, DC-13 (Ue = 250 V), le = 0.1 A conforming to EN/IEC 60947-5-1 appendix A		
[Ui] rated insulation voltage	300 V conforming to UL 508 500 V (pollution degree 3) conforming to IEC 60947-1 300 V conforming to CSA C22.2 No 14		
[Uimp] rated impulse withstand voltage	6 kV conforming to IEC 60664 6 kV conforming to IEC 60947-1		
Short-circuit protection	10 A cartridge fuse, type gG		
Electrical durability	5000000 cycles, DC-13 120 V, 4 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 5000000 cycles, DC-13 24 V, 10 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 5000000 cycles, DC-13 48 V, 7 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C		
Width	31 mm		
Height	65 mm		
Depth	30 mm		
Net weight	0.07 kg		
Environment Product compatibility	XCKP		
Ambient air temperature for operation	-2570 °C		
Ambient air temperature for storage	-4070 °C		
Packing Units			
Unit Type of Package 1	PCE		
Number of Units in Package 1	1		
Package 1 Weight	60.0 g		
Package 1 Height	4.0 cm		
Package 1 width	4.0 cm		
Package 1 Length	7.6 cm		
Unit Type of Package 2	P06		
Number of Units in Package 2	1296		
Package 2 Weight	96.132 kg		
Package 2 Height	77.0 cm		
Package 2 width	60.0 cm		
Package 2 Length	80.0 cm		
Unit Type of Package 3	S02		
Number of Units in Package 3	81		

5.42 kg 15.0 cm

30.0 cm

40.0 cm

Package 3 Weight

Package 3 Height

Package 3 width

Package 3 Length

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
Contractual warranty	

Warranty	18 months	
----------	-----------	--